

SKYREACH Patio Door Performance Grade

NAFS is a new, inclusive testing standard for windows, doors and skylights that addresses product performance and quality requirements. This more refined performance testing, rating and labelling system synchronizes Canadian and American fenestration standards, and is called the "Harmonized Standard" in the Building Code. For more performance test result ratings, contact your SKYREACH sales representative.

PD02/03 PERFORMANCE as per NAFS-08

21-Aug-14

No.	Description:	PD02/03					SIZE	Reinforcement
		Air	Water	Structure	Class	PG		
1	PD02-OX	A2	DP35	DP35	R	DP35	71.625"x79.5"	Aluminum
2	PD02-XX	A2	DP30	DP30	R	DP30	71.625"x79.5"	Aluminum
3	PD02-OX	A3	DP35	DP35	LC	DP35	95.625"x95.5"	Galv. Steel

PD04 PERFORMANCE as per NAFS-08

No.	Description:	PD04					SIZE	Reinforcement
		Air	Water	Structure	Class	PG		
1	PD04-OX	A3	DP30	DP30	R	DP30	71.625"x79.5"	Aluminum
2	PD04-OX IMPACT	A3	DP50	DP50	LC	DP50	95.625"x95.5"	Steel + Al.

PD05 PERFORMANCE as per NAFS-08

No.	Description:	PD05					SIZE	Reinforcement
		Air	Water	Structure	Class	PG		
1	PD05-OX Welded	A3	DP30	DP30	R	DP30	71.625"x79.5"	Aluminum
2	PD05-OX Mech. Joint	A3	DP35	DP35	R	DP35	71.625"x79.5"	Aluminum
3	PD05-XX	A2	DP25	DP25	R	DP25	71.625"x79.5"	Aluminum